


**VOLTA TECHNICAL DATA**

Product: **Volta RMW**  
 Description: Round Reinforced  
 Material: Volta MW, Beige  
 Hardness: 95 A / 46 D  
 Temp. Range: -30° C to 60° C  
 FDA / USDA Accepted

Coefficient of Friction:  
 Steel: 0.36  
 Aluminum: 0.36



**RMW**

BELT TYPE	DIAMETER Ø mm	WEIGHT kg / m	MIN. PULLEY Ø mm	MAX. WORK LOAD kg	PULLFORCE (KG) AT PRETENSION			DRILL BIT
					0.5 %	1%	1.5%	
RMW-6.3	6.3	0.04	75	27	10	20	NR	I
RMW-8	8.0	0.06	95	42	17	35	NR	I
RMW-9.5	9.5	0.09	110	63	18	37	55	I
RMW-12.5	12.5	0.15	150	105	28	57	85	II
RMW-15	15	0.21	175	153	30	60	90	II
RMW-18	18	0.31	210	215	32	64	96	III

Notes

1. Pull Force in tables relate to Steel and Aluminum pulleys. Multiply given values by 0.7 for wet pulleys.
2. All values are nominal and to the best of our experience are true and accurate.
3. NR = Not Recommended